


505002

## NANOSTEP ROUND XS

Round shape wall-recessed luminaire for outdoor installation. Body and frontal cover in hard anodized aluminum with phosphochromatised and polyester powder coating, tempered safety glass, moulded silicone gasket. Asymmetrical oval wide light distribution. Remote constant current max 700mA driver needed, with 1 CREE XP-L LED. IP68 rating.



### 350 mA - LED POWER 1.2W

light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
<b>2700°K warm-white</b>			
high-power led	8°	130	108.33
high-power led	40°	120	100.00
<b>3000°K warm-white</b>			
high-power led	8°	135	112.50
high-power led	40°	125	104.17
<b>4000°K neutral-white</b>			
high-power led	8°	145	120.83
high-power led	40°	135	112.50

### Finish color options:



### Technical features



### Technical data

Wattage	MAX 2.5 WATT
IP Rating	IP68
IK Rating	IK08
Material	Hard anodized aluminum body and trim
Coating	Polyester powder coating with phosphochromating pre-finish
IK Rating	1 x CREE XP-L LED
Screws	Stainless steel
Remote driver	Constant current max 700mA
Gasket	Silicone rubber
Glass	Tempered
Cable gland	M12
Power cable	0.3 mt. power cable included
Gross weight	1,00 Kg

#### 500 mA - LED POWER 1.7W

light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
<b>2700°K warm-white</b>			
high-power led	 8°	184	108.33
high-power led	 40°	170	100.00
<b>3000°K warm-white</b>			
high-power led	 8°	191	112.50
high-power led	 40°	177	104.17
<b>4000°K neutral-white</b>			
high-power led	 8°	205	120.83
high-power led	 40°	191	112.50

#### 700 mA - LED POWER 2.5W

light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
<b>2700°K warm-white</b>			
high-power led	 8°	271	108.33
high-power led	 40°	250	100.00
<b>3000°K warm-white</b>			
high-power led	 8°	281	112.50
high-power led	 40°	260	104.17
<b>4000°K neutral-white</b>			
high-power led	 8°	302	120.83
high-power led	 40°	281	112.50

#### remote driver selection

brand	manufacturer code	type	watt	IP rate	numbers of fixtures
ALVIT Italy	AL1435S-IP	constant current 350mA	14W	IP67	min 1 - max 8
ALVIT Italy	AL1450S-IP	constant current 500mA	14W	IP67	min 1 - max 6
ALVIT Italy	AL1470S-IP	constant current 700mA	14W	IP67	min 1 - max 4

