

## Fittings / LED Floodlights

### Skyline Slim+ 70W LED Floodlight - 4000K



The Skyline Slim+ LED Floodlight is suitable for a wide range of applications. Available in a vast range of wattages, this low energy floodlight is ideal for any lighting project, big or small.

- Marine Grade Aluminium body.
- Fully encapsulated IP65 TUV certified driver.
- 10/20/30/50W versions are genuine replacements for Halogen Floodlights.
- 70/100/150/200W versions are genuine replacements for Metal Halide Floodlights.
- Average 8M detection range for PIR Floods.

## Technical Specification

		Without PIR Symmetric							
		10W	20W	30W	50W	70W	100W	150W	200W
A	154mm	142mm	158mm	200mm	252mm	318mm	377mm	430mm	
B	83mm	84mm	83mm	117mm	129mm	176mm	180mm	185mm	
C	39mm	33mm	34mm	44mm	48mm	60mm	60mm	60mm	

  

		Asymmetric Without PIR			
		50W	70W	100W	200W
A	232mm	312mm	312mm	353mm	408mm
B	124mm	230mm	271mm	302mm	322mm
C	48mm	62mm	60mm	60mm	60mm

  

		With PIR Symmetric			
		10W	20W	30W	70W
A	175mm	185mm	200mm	230mm	300mm
B	112mm	120mm	137mm	170mm	200mm
C	68mm	68mm	72mm	72mm	72mm

Product Code

10984

## Reference

Guarantee

5 Years

EAN

5013588109848

Commodity Code

9405423990

Country of Origin

CN

UNSPSC Code

39111626

## Technical Specification

Volts (V)	240
Watts (W)	70
Colour Temp (K)	4000
Dimmable?	No
Lumens (lm)	8400
Life Hours	50000
Beam Angle	110°
CRI (ra)	80
Switching Cycles	25000
Frequency (Hz)	50/60
LED Drive Current	715mA
Energy Consumption (kWh/1000h)	70
IP Rating	IP65
Impact Protection	IK8

## Dimensions

Height (mm)	259
Width (mm)	229
Depth (mm)	48

## Packaging Information

Single Carton Height (mm)	232
Single Carton Width (mm)	58
Single Carton Depth (mm)	256
Single Carton Weight (kg)	1.51502
Individual Volume	0.00344
Outer Box Qty	6
Outer Box Height (mm)	365
Outer Box Width (mm)	236
Outer Box Depth (mm)	262
Outer Box Weight (kg)	9.55129