

## Fittings / LED Floodlights


### Skyline Slim+ 100W LED Floodlight - 4000K



The Skyline Slim+ LED Floodlight is suitable for a wide range of applications. Available in a vast range of wattages, this low energy floodlight is ideal for any lighting project, big or small.

- Marine Grade Aluminium body.
- Fully encapsulated IP65 TUV certified driver.
- 10/20/30/50W versions are genuine replacements for Halogen Floodlights.
- 70/100/150/200W versions are genuine replacements for Metal Halide Floodlights.
- Average 8M detection range for PIR Floods.

## Technical Specification



Without PIR Symmetric								
	10W	20W	30W	50W	70W	100W	150W	200W
A	134mm	142mm	158mm	200mm	229mm	318mm	377mm	430mm
B	33mm	34mm	38mm	47mm	52mm	75mm	90mm	105mm
C	32mm	32mm	34mm	44mm	48mm	60mm	60mm	60mm

Asymmetric Without PIR					
	50W	70W	100W	150W	200W
A	232mm	315mm	325mm	353mm	408mm
B	26mm	23mm	27mm	30mm	32mm
C	48mm	62mm	60mm	60mm	60mm

With PIR Symmetric					
	10W	20W	30W	50W	70W
A	175mm	185mm	200mm	230mm	260mm
B	112mm	120mm	137mm	170mm	200mm
C	68mm	68mm	72mm	72mm	72mm

**Product Code**

10990

## Reference

**Guarantee**

5 Years

**EAN**

5013588109909

**Commodity Code**

9405423990

**Country of Origin**

CN

**UNSPSC Code**

39111626

## Technical Specification

Volts (V)	240
Watts (W)	100
Colour Temp (K)	4000
Dimmable?	No
Lumens (lm)	12000
Life Hours	50000
Beam Angle	110°
CRI (ra)	80
Switching Cycles	25000
Frequency (Hz)	50/60
LED Drive Current	930mA
Energy Consumption (kWh/1000h)	100
IP Rating	IP65
Impact Protection	IK8

## Dimensions

Height (mm)	318
Width (mm)	276
Depth (mm)	60

## Packaging Information

Single Carton Height (mm)	280
Single Carton Width (mm)	70
Single Carton Depth (mm)	323
Single Carton Weight (kg)	3.28437
Individual Volume	0.00633
Outer Box Qty	4
Outer Box Height (mm)	292
Outer Box Width (mm)	284
Outer Box Depth (mm)	329
Outer Box Weight (kg)	13.6759