

Fittings / LED Floodlights

Skyline Slim+ 200W LED Floodlight - 4000K



The Skyline Slim+ LED Floodlight is suitable for a wide range of applications. Available in a vast range of wattages, this low energy floodlight is ideal for any lighting project, big or small.

- Marine Grade Aluminium body.
- Fully encapsulated IP65 TUV certified driver.
- 10/20/30/50W versions are genuine replacements for Halogen Floodlights.
- 70/100/150/200W versions are genuine replacements for Metal Halide Floodlights.
- Average 8M detection range for PIR Floods.

Technical Specification

Without PIR Symmetric									
	10W	20W	30W	50W	70W	100W	150W	200W	
A	134mm	142mm	158mm	200mm	229mm	318mm	377mm	430mm	
B	83mm	84mm	138mm	170mm	229mm	276mm	300mm	305mm	
C	32mm	32mm	34mm	44mm	48mm	60mm	60mm	60mm	

Asymmetric Without PIR					
	50W	70W	100W	150W	200W
A	232mm	315mm	325mm	353mm	408mm
B	124mm	220mm	277mm	300mm	302mm
C	48mm	62mm	60mm	60mm	60mm

With PIR Symmetric					
	10W	20W	30W	50W	70W
A	170mm	180mm	200mm	230mm	300mm
B	112mm	120mm	137mm	170mm	200mm
C	68mm	68mm	72mm	72mm	72mm

Product Code

10992

Reference

Guarantee

5 Years

EAN

5013588109923

Commodity Code

9405423990

Country of Origin

CN

UNSPSC Code

39111626

Technical Specification

Volts (V)	240
Watts (W)	200
Colour Temp (K)	4000
Dimmable?	No
Lumens (lm)	24000
Life Hours	50000
Beam Angle	110°
CRI (ra)	80
Switching Cycles	25000
Frequency (Hz)	50/60
LED Drive Current	1850mA
Energy Consumption (kWh/1000h)	200
IP Rating	IP65
Impact Protection	IK8

Dimensions

Height (mm)	410
Width (mm)	355
Depth (mm)	60

Packaging Information

Single Carton Height (mm)	355
Single Carton Width (mm)	70
Single Carton Depth (mm)	416
Single Carton Weight (kg)	5.12888
Individual Volume	0.01034
Outer Box Qty	2
Outer Box Height (mm)	360
Outer Box Width (mm)	148
Outer Box Depth (mm)	424
Outer Box Weight (kg)	10.70593