

Fittings / LED Floodlights


Skyline Virtus 50/75/100W Wattage Switchable Asymmetric Floodlight - 4000K



Designed and engineered in the UK specifically to meet the requirements for sports lighting and to reduce light pollution levels. The Skyline Virtus is a high specification floodlight, wattage switchable as standard with a 50,000 hour lifespan, 7 year warranty and 2 year on site warranty.

- Wattage Switchable.
- Perfect for sports, building facade's, landscape, security & car park lighting.
- Asymmetric distribution, low light pollution.
- Aerodynamic, streamlined design for reduced windage.
- Air pressure equalisation feature to eliminate capillary effect.
- Nichia GRT-V1 LED.
- Surge protected 10,000V.
- Fully encapsulated IP54 TUV certified driver.
- Supplied pre-flexed (1.5M).
- Robust construction, supplied with standard universal mounting bracket.

Technical Specification



	50/75/100W	100/150/200W	100/225/300W
A	353mm	447mm	495mm
B	297mm	359mm	406mm
C	65mm	75mm	75mm

Product Code 11485

Reference

Guarantee	7 Years
EAN	5013588114859
Commodity Code	9405423990
Country of Origin	CN
UNSPSC Code	39111626

Technical Specification

Volts (V)	110/240
Watts (W)	50/75/100
Colour Temp (K)	4000
Dimmable?	No
Lumens (lm)	7700-15450
Life Hours	50000
Energy Rating	D
CRI (ra)	80
Switching Cycles	100000
Frequency (Hz)	50/60
LED Drive Current	130mA
Energy Consumption (kWh/1000h)	100
IP Rating	IP66
Impact Protection	IK8

Dimensions

Height (mm)	353
Width (mm)	287
Depth (mm)	65

Packaging Information

Single Carton Height (mm)	375
Single Carton Width (mm)	320
Single Carton Depth (mm)	90
Single Carton Weight (kg)	3.2
Individual Volume	0.0108
Outer Box Qty	1
Outer Box Height (mm)	375
Outer Box Width (mm)	320
Outer Box Depth (mm)	90
Outer Box Weight (kg)	3.5