

## Fittings / LED Floodlights


# Skyline Virtus 150/225/300W Wattage Switchable Asymmetric Floodlight - 4000K



Designed and engineered in the UK specifically to meet the requirements for sports lighting and to reduce light pollution levels. The Skyline Virtus is a high specification floodlight, wattage switchable as standard with a 50,000 hour lifespan, 7 year warranty and 2 year on site warranty.

- Wattage Switchable.
- Perfect for sports, building facade's, landscape, security & car park lighting.
- Asymmetric distribution, low light pollution.
- Aerodynamic, streamlined design for reduced windage.
- Air pressure equalisation feature to eliminate capillary effect.
- Nichia GRT-V1 LED.
- Surge protected 10,000V.
- Fully encapsulated IP54 TUV certified driver.
- Supplied pre-flexed (1.5M).
- Robust construction, supplied with standard universal mounting bracket.

## Technical Specification



	50/75/100W	100/150/200W	100/225/300W
A	353mm	447mm	495mm
B	297mm	359mm	406mm
C	65mm	75mm	75mm

**Product Code** 11491

### Reference

<b>Guarantee</b>	7 Years
<b>EAN</b>	5013588114910
<b>Commodity Code</b>	9405423990
<b>Country of Origin</b>	CN
<b>UNSPSC Code</b>	39111626

## Technical Specification

Volts (V)	110/240
Watts (W)	150/225/300
Colour Temp (K)	4000
Dimmable?	No
Lumens (lm)	22400-46050
Life Hours	50000
Energy Rating	D
CRI (ra)	80
Switching Cycles	100000
Frequency (Hz)	50/60
LED Drive Current	132mA
Energy Consumption (kWh/1000h)	300
IP Rating	IP66
Impact Protection	IK8

## Dimensions

Height (mm)	495
Width (mm)	417
Depth (mm)	75

## Packaging Information

Single Carton Height (mm)	525
Single Carton Width (mm)	450
Single Carton Depth (mm)	115
Single Carton Weight (kg)	7.1
Individual Volume	0.02717
Outer Box Qty	1
Outer Box Height (mm)	525
Outer Box Width (mm)	450
Outer Box Depth (mm)	115
Outer Box Weight (kg)	7.4