

## Fittings / LED Street Lights

# Alto 100W LED IP66 Street Light with Nema Socket - 4000K




The Alto LED Street Light offers flexibility, it is suitable for use in many locations, including rural towns, car parks and access roads. The Alto is available in a variety of wattages for a variety of applications, and is a robust weatherproof construction meeting an IP66 protection rating.

- 150 lm/W.
- Genuine Replacement for 70W Son or Metal Halide.
- Ideal for car parks and pedestrian walkways.
- Reduced light pollution.
- Precision lens system directs light only where it is needed, reducing overspill.
- Aerodynamic design for reduced windage.
- 60mm side or post top entry.
- 3 Pin Nema socket with blanking plug as standard.

## Technical Specification

	70W	50W	70W	100W	150W	
Length (mm)	SE 523 / PTE 409	SE 523 / PTE 409	SE 629 / PTE 515	SE 629 / PTE 515	SE 724 / PTE 610	SE Side Entry PTE Post Top Entry
Width (mm)	SE 146 / PTE 345	SE 346 / PTE 146	SE 174 / PTE 174	SE 174 / PTE 174	SE 194 / PTE 194	
Height (mm)	SE 134 / PTE 348	SE 134 / PTE 248	SE 135 / PTE 249	SE 135 / PTE 249	SE 137 / PTE 251	



**Product Code**

11703

## Reference

**Guarantee**

7 Years

**EAN**

5013588117034

**Commodity Code**

9405423990

**Country of Origin**

CN

**UNSPSC Code**

39111608

## Technical Specification

Volts (V)	220/240
Watts (W)	100
Colour Temp (K)	4000
Dimmable?	No
Lumens (lm)	15000
Life Hours	50000
CRI (ra)	85
Switching Cycles	80000
Frequency (Hz)	50/60
LED Drive Current	117mA
Energy Consumption (kWh/1000h)	100
IP Rating	IP66
Impact Protection	IK8

## Dimensions

Height (mm)	135
Width (mm)	174
Length (mm)	629

## Packaging Information

Single Carton Height (mm)	135
Single Carton Width (mm)	185
Single Carton Depth (mm)	510
Single Carton Weight (kg)	3.3
Individual Volume	0.01274
Outer Box Qty	1