

Fittings / LED Street Lights

Alto 150W LED IP66 Street Light with Nema Socket - 4000K




The Alto LED Street Light offers flexibility, it is suitable for use in many locations, including rural towns, car parks and access roads. The Alto is available in a variety of wattages for a variety of applications, and is a robust weatherproof construction meeting an IP66 protection rating.

- 150 lm/W.
- Genuine Replacement for 70W Son or Metal Halide.
- Ideal for car parks and pedestrian walkways.
- Reduced light pollution.
- Precision lens system directs light only where it is needed, reducing overspill.
- Aerodynamic design for reduced windage.
- 60mm side or post top entry.
- 3 Pin Nema socket with blanking plug as standard.

Technical Specification

	70W	90W	120W	150W	180W	
Length (mm)	SE 523 / PTE 409	SE 523 / PTE 409	SE 629 / PTE 515	SE 629 / PTE 515	SE 724 / PTE 610	SE Side Entry PTE Post Top Entry
Width (mm)	SE 146 / PTE 345	SE 146 / PTE 345	SE 174 / PTE 174	SE 174 / PTE 174	SE 194 / PTE 194	
Height (mm)	SE 134 / PTE 248	SE 134 / PTE 248	SE 135 / PTE 249	SE 135 / PTE 249	SE 137 / PTE 251	



Product Code 11704

Reference

Guarantee 7 Years

EAN 5013588117041

Commodity Code 9405423990

Country of Origin CN

UNSPSC Code 39111608

Technical Specification

Volts (V)	220/240
Watts (W)	150
Colour Temp (K)	4000
Dimmable?	No
Lumens (lm)	22500
Life Hours	50000
CRI (ra)	85
Switching Cycles	80000
Frequency (Hz)	50/60
LED Drive Current	122mA
Energy Consumption (kWh/1000h)	150
IP Rating	IP66
Impact Protection	IK8

Dimensions

Height (mm)	137
Width (mm)	194
Length (mm)	724

Packaging Information

Single Carton Height (mm)	140
Single Carton Width (mm)	205
Single Carton Depth (mm)	605
Single Carton Weight (kg)	4.3
Individual Volume	0.01736
Outer Box Qty	1