



Fittings / Downlights

Arial Pro 10W IP44 LED CCT Downlight



The Arial Pro LED Downlight is a sleek looking luminaire designed to replace cumbersome CFL fittings. With a 7 year guarantee across both the IP44 & IP65 range, the Arial Pro can be installed in a variety of applications with the confidence of knowing this product will stand the test of time.

- Switchable colour temperature 3000/4000/6000K.
- Ideal for home and office environments.
- Equivalent up to 2x26W fluorescent.
- Tool Free Plug & Play.
- IP44.

2-20mm
Cut Out

Technical Specification

	9W	16W	20W
Diameter	115mm	190mm	240mm
Height	70.5mm	102mm	117mm
Cut Out	90mm	160mm	200mm

Product Code	10950
Reference	
Guarantee	7 Years
EAN	5013588109503
Commodity Code	9405409990
Country of Origin	CN
UNSPSC Code	39111515

www.belllighting.co.uk







Technical Specification

Watts (W)	10
Volts (V)	220/240
Colour Temp (K)	3000/4000/6000
Lumens (lm)	910
Lumens per Watt (lm/W)	91
CRI (ra)	85
Frequency (Hz)	50/60
LED Drive Current	230mA
Energy Consumption (kWh/1000h)	10
Life Hours	50000
Switching Cycles	25000
IP Rating	IP44
Dimmable?	No
Dimensions	
Height (mm)	71
Diameter (mm)	115
Downlight Cut Out (mm)	90-95
Downlight Cut Out (mm) Packaging Information	90-95
	90-95 71
Packaging Information	
Packaging Information Height (mm)	71
Packaging Information Height (mm) Diameter (mm)	71 115
Packaging Information Height (mm) Diameter (mm) Downlight Cut Out (mm)	71 115 90-95
Packaging Information Height (mm) Diameter (mm) Downlight Cut Out (mm) Individual Product Weight (kg)	71 115 90-95 0.195
Packaging InformationHeight (mm)Diameter (mm)Downlight Cut Out (mm)Individual Product Weight (kg)Single Carton Height (mm)	71 115 90-95 0.195 90
Packaging InformationHeight (mm)Diameter (mm)Downlight Cut Out (mm)Individual Product Weight (kg)Single Carton Height (mm)Single Carton Width (mm)	71 115 90-95 0.195 90 135
Packaging InformationHeight (mm)Diameter (mm)Downlight Cut Out (mm)Individual Product Weight (kg)Single Carton Height (mm)Single Carton Width (mm)Single Carton Depth (mm)	71 115 90-95 0.195 90 135 170
Packaging InformationHeight (mm)Diameter (mm)Downlight Cut Out (mm)Individual Product Weight (kg)Single Carton Height (mm)Single Carton Width (mm)Single Carton Depth (mm)Single Carton Weight (kg)	71 115 90-95 0.195 90 135 170 0.275
Packaging InformationHeight (mm)Diameter (mm)Downlight Cut Out (mm)Individual Product Weight (kg)Single Carton Height (mm)Single Carton Width (mm)Single Carton Depth (mm)Single Carton Weight (kg)Individual Volume	71 115 90-95 0.195 90 135 170 0.275 0.00207
Packaging InformationHeight (mm)Diameter (mm)Downlight Cut Out (mm)Individual Product Weight (kg)Single Carton Height (mm)Single Carton Width (mm)Single Carton Depth (mm)Single Carton Weight (kg)Individual VolumeInner Box Qty	71 115 90-95 0.195 90 135 170 0.275 0.00207 1
Packaging InformationHeight (mm)Diameter (mm)Downlight Cut Out (mm)Individual Product Weight (kg)Single Carton Height (mm)Single Carton Width (mm)Single Carton Depth (mm)Single Carton Weight (kg)Individual VolumeInner Box QtyOuter Box Qty	71 115 90-95 0.195 90 135 170 0.275 0.00207 1 30
Packaging InformationHeight (mm)Diameter (mm)Downlight Cut Out (mm)Individual Product Weight (kg)Single Carton Height (mm)Single Carton Width (mm)Single Carton Depth (mm)Single Carton Weight (kg)Individual VolumeInner Box QtyOuter Box Height (mm)	71 115 90-95 0.195 90 135 170 0.275 0.00207 1 30 475
Packaging InformationHeight (mm)Diameter (mm)Downlight Cut Out (mm)Individual Product Weight (kg)Single Carton Height (mm)Single Carton Width (mm)Single Carton Depth (mm)Single Carton Weight (kg)Individual VolumeInner Box QtyOuter Box Height (mm)Outer Box Width (mm)	71 115 90-95 0.195 90 135 170 0.275 0.00207 1 30 475 285

www.belllighting.co.uk

