



Fittings / Downlights


Arial Pro 16W IP44 LED CCT Downlight



The Arial Pro LED Downlight is a sleek looking luminaire designed to replace cumbersome CFL fittings. With a 7 year guarantee across both the IP44 & IP65 range, the Arial Pro can be installed in a variety of applications with the confidence of knowing this product will stand the test of time.

- Switchable colour temperature 3000/4000/6000K.
- Ideal for home and office environments.
- Equivalent up to 2x26W fluorescent.
- Tool Free Plug & Play.
- IP44.

Technical Specification



	9W	16W	20W
Diameter	115mm	190mm	240mm
Height	70.5mm	102mm	117mm
Cut Out	90mm	160mm	200mm

Duaduat Cada	10051
Product Code	10951

Reference

Guarantee	7 Years
EAN	5013588109510
Commodity Code	9405409990
Country of Origin	CN
UNSPSC Code	39111515







Technical Specification

Watts (W)	16
Volts (V)	220/240
Colour Temp (K)	3000/4000/6000
Lumens (lm)	1660
Lumens per Watt (lm/W)	104
CRI (ra)	85
Frequency (Hz)	50/60
LED Drive Current	400mA
Energy Consumption (kWh/1000h)	16
Life Hours	50000
Switching Cycles	25000
IP Rating	IP44
Dimmable?	No
Dimensions	
	102
Height (mm)	102
Diameter (mm)	190
Downlight Cut Out (mm)	160-170
Packaging Information	160-170
	102
Packaging Information	
Packaging Information Height (mm)	102
Packaging Information Height (mm) Diameter (mm)	102 190
Packaging Information Height (mm) Diameter (mm) Downlight Cut Out (mm)	102 190 160-170
Packaging Information Height (mm) Diameter (mm) Downlight Cut Out (mm) Individual Product Weight (kg)	102 190 160-170 0.4
Packaging Information Height (mm) Diameter (mm) Downlight Cut Out (mm) Individual Product Weight (kg) Single Carton Height (mm)	102 190 160-170 0.4 126
Packaging Information Height (mm) Diameter (mm) Downlight Cut Out (mm) Individual Product Weight (kg) Single Carton Height (mm) Single Carton Width (mm)	102 190 160-170 0.4 126 200
Packaging Information Height (mm) Diameter (mm) Downlight Cut Out (mm) Individual Product Weight (kg) Single Carton Height (mm) Single Carton Depth (mm)	102 190 160-170 0.4 126 200 200
Packaging Information Height (mm) Diameter (mm) Downlight Cut Out (mm) Individual Product Weight (kg) Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg)	102 190 160-170 0.4 126 200 200 0.55
Packaging Information Height (mm) Diameter (mm) Downlight Cut Out (mm) Individual Product Weight (kg) Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume	102 190 160-170 0.4 126 200 200 0.55
Packaging Information Height (mm) Diameter (mm) Downlight Cut Out (mm) Individual Product Weight (kg) Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty	102 190 160-170 0.4 126 200 200 0.55 0.00504
Packaging Information Height (mm) Diameter (mm) Downlight Cut Out (mm) Individual Product Weight (kg) Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty Outer Box Qty	102 190 160-170 0.4 126 200 200 0.55 0.00504 1
Packaging Information Height (mm) Diameter (mm) Downlight Cut Out (mm) Individual Product Weight (kg) Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty Outer Box Qty Outer Box Height (mm)	102 190 160-170 0.4 126 200 200 0.55 0.00504 1 12 400
Packaging Information Height (mm) Diameter (mm) Downlight Cut Out (mm) Individual Product Weight (kg) Single Carton Height (mm) Single Carton Depth (mm) Single Carton Weight (kg) Individual Volume Inner Box Qty Outer Box Qty Outer Box Width (mm) Outer Box Width (mm)	102 190 160-170 0.4 126 200 200 0.55 0.00504 1 12 400 415

