



## Fittings / Downlights


## Arial Pro 16W LED CCT IP44 Downlight in Emergency (1Y)



The Arial Pro LED Downlight is a sleek looking luminaire designed to replace cumbersome CFL fittings. With a 7 year guarantee across both the IP44 & IP65 range, the Arial Pro can be installed in a variety of applications with the confidence of knowing this product will stand the test of time.

- Switchable colour temperature 3000/4000/6000K.
- Ideal for home and office environments.
- Equivalent up to 2x26W fluorescent.
- Tool Free Plug & Play.
- IP44.

## **Technical Specification**



	9W	16W	20W
Diameter	115mm	190mm	240mm
Height	70.5mm	102mm	117mm
Cut Out	90mm	160mm	200mm

Product Code	10957	
Reference		
Guarantee	7 Years	
EAN	5013588109572	
Commodity Code	9405409990	
Country of Origin	CN	
UNSPSC Code	39111515	

www.belllighting.co.uk







## **Technical Specification**

Watts (W)	16
Volts (V)	220/240
Colour Temp (K)	3000/4000/6000
Lumens (lm)	1660
Lumens per Watt (lm/W)	104
CRI (ra)	85
Frequency (Hz)	50/60
LED Drive Current	400mA
Energy Consumption (kWh/1000h)	16
Life Hours	50000
Switching Cycles	25000
IP Rating	IP44
Dimensions	
Height (mm)	102
Diameter (mm)	190
Downlight Cut Out (mm)	160-170
Packaging Information	
r dendynig information	
Height (mm)	102
	102 190
Height (mm)	
Height (mm) Diameter (mm)	190
Height (mm) Diameter (mm) Downlight Cut Out (mm)	190 160-170
Height (mm) Diameter (mm) Downlight Cut Out (mm) Individual Product Weight (kg)	190   160-170   1.587
Height (mm) Diameter (mm) Downlight Cut Out (mm) Individual Product Weight (kg) Single Carton Height (mm)	190     160-170     1.587     126
Height (mm)Diameter (mm)Downlight Cut Out (mm)Individual Product Weight (kg)Single Carton Height (mm)Single Carton Width (mm)	190     160-170     1.587     126     200
Height (mm)Diameter (mm)Downlight Cut Out (mm)Individual Product Weight (kg)Single Carton Height (mm)Single Carton Width (mm)Single Carton Depth (mm)	190     160-170     1.587     126     200     200
Height (mm)Diameter (mm)Downlight Cut Out (mm)Individual Product Weight (kg)Single Carton Height (mm)Single Carton Width (mm)Single Carton Depth (mm)Single Carton Weight (kg)	190     160-170     1.587     126     200     200     2.15
Height (mm)Diameter (mm)Downlight Cut Out (mm)Individual Product Weight (kg)Single Carton Height (mm)Single Carton Width (mm)Single Carton Depth (mm)Single Carton Weight (kg)Individual Volume	190     160-170     1.587     126     200     200     2.15     0.00504
Height (mm)Diameter (mm)Downlight Cut Out (mm)Individual Product Weight (kg)Single Carton Height (mm)Single Carton Width (mm)Single Carton Depth (mm)Single Carton Weight (kg)Individual VolumeInner Box Qty	190     160-170     1.587     126     200     200     2.00     2.15     0.00504     1
Height (mm)Diameter (mm)Downlight Cut Out (mm)Individual Product Weight (kg)Single Carton Height (mm)Single Carton Width (mm)Single Carton Depth (mm)Single Carton Weight (kg)Individual VolumeInner Box QtyOuter Box Qty	190     160-170     1.587     126     200     200     200     2.15     0.00504     1     12
Height (mm)Diameter (mm)Downlight Cut Out (mm)Individual Product Weight (kg)Single Carton Height (mm)Single Carton Width (mm)Single Carton Depth (mm)Single Carton Weight (kg)Individual VolumeInner Box QtyOuter Box Height (mm)	190     160-170     1.587     126     200     200     2.15     0.00504     1     12     400

www.belllighting.co.uk

