

## Fittings / LED Warehouse Lighting

### Illumina Atlas 90/120/150W LED High Bay - 120° Lens - 4000K



The Illumina Atlas Switchable Wattage High Bay is a highly efficient versatile LED luminaire, ideally suited to a wide range of industrial applications for both new installations and retrofit applications.

- 60-200 Switchable Wattages.
- Seoul Semiconductor LED.
- Plug-in PIR & microwave sensors available.
- Sensor parameters set by remote control.
- Genuine Replacement for 250-600W Metal Halide or Sodium.
- Perfect for warehousing, large retail and factories.
- Emergency kit available.
- 145 Lm/W.

## Technical Specification



|          | 100w  | 150w  | 200w  |
|----------|-------|-------|-------|
| Diameter | 245mm | 245mm | 294mm |
| Height   | 159mm | 174mm | 174mm |

**Product Code** 11452

### Reference

|                            |                                     |
|----------------------------|-------------------------------------|
| <b>Guarantee</b>           | 7 Years                             |
| <b>EAN</b>                 | 5013588114521                       |
| <b>Commodity Code</b>      | 9405423990                          |
| <b>Country of Origin</b>   | CN                                  |
| <b>UNSPSC Code</b>         | 39111546                            |
| <b>Product Application</b> | Commercial, Industrial, Warehousing |
| <b>Product Category</b>    | High Bay                            |

## Technical Specification

|                                |             |
|--------------------------------|-------------|
| Watts (W)                      | 90/120/150  |
| Volts (V)                      | 100/240     |
| Equivalent Watts (W)           | 400         |
| Colour Temp (K)                | 4000        |
| Lumens (lm)                    | 14000-21000 |
| Lumens per Watt (lm/W)         | 140-156     |
| CRI (ra)                       | 80          |
| Frequency (Hz)                 | 50/60       |
| Energy Consumption (kWh/1000h) | 150         |
| Life Hours                     | 50000       |
| Switching Cycles               | 100000      |
| Impact Protection              | IK10        |
| IP Rating                      | IP65        |
| Dimmable?                      | Yes         |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 174 |
| Diameter (mm) | 245 |

## Packaging Information

|                                |         |
|--------------------------------|---------|
| Height (mm)                    | 174     |
| Diameter (mm)                  | 245     |
| Individual Product Weight (kg) | 2       |
| Single Carton Height (mm)      | 290     |
| Single Carton Width (mm)       | 290     |
| Single Carton Depth (mm)       | 155     |
| Single Carton Weight (kg)      | 2.6     |
| Individual Volume              | 0.01304 |
| Outer Box Qty                  | 1       |