

## Fittings / LED Bulkheads


# Aqua1 9/14/18W LED CCT White Bulkhead in Emergency



This cost-effective, colour switchable bulkhead is IP65 as standard, with the benefits of a high transmission frosted diffuser and rear, side & BESA Box cable entry. It is an ideal replacement for 28W 2D fittings.

- CCT Cool White / Warm White / Daylight (3/4/6000K).
- High transmission frosted diffuser.
- IP65 sealed fitting.
- Rear, Side & BESA Box cable entry.
- Emergency, microwave and corridor dimming options.

## Technical Specification



|                     |       |
|---------------------|-------|
| <b>Product Code</b> | 11601 |
|---------------------|-------|

### Reference

|                          |               |
|--------------------------|---------------|
| <b>Guarantee</b>         | 7 Years       |
| <b>EAN</b>               | 5013588116013 |
| <b>Commodity Code</b>    | 9405109890    |
| <b>Country of Origin</b> | CN            |
| <b>UNSPSC Code</b>       | 39111612      |

## Technical Specification

|                                |                |
|--------------------------------|----------------|
| Watts (W)                      | 9/14/18        |
| Equivalent Watts (W)           | 16-38          |
| Volts (V)                      | 220/240        |
| Colour Temp (K)                | 3000/4000/6000 |
| Lumens (lm)                    | 870-1700       |
| Lumens per Watt (lm/W)         | 94-97          |
| Emergency Lumen Output (lm)    | 145            |
| Candelas (cd)                  | 360-675        |
| CRI (Ra)                       | 80             |
| Frequency (Hz)                 | 50             |
| LED Drive Current              | 130mA          |
| Energy Consumption (kWh/1000h) | 18             |
| Life Hours                     | 50000          |
| Switching Cycles               | 30000          |
| Energy Rating                  | C              |
| Impact Protection              | IK10           |
| IP Rating                      | IP65           |

## Dimensions

|               |     |
|---------------|-----|
| Depth (mm)    | 115 |
| Diameter (mm) | 340 |

## Packaging Information

|                                |         |
|--------------------------------|---------|
| Depth (mm)                     | 115     |
| Diameter (mm)                  | 340     |
| Individual Product Weight (kg) | 0.982   |
| Single Carton Height (mm)      | 113     |
| Single Carton Width (mm)       | 340     |
| Single Carton Depth (mm)       | 343     |
| Single Carton Weight (kg)      | 1.253   |
| Individual Volume              | 0.01318 |
| Inner Box Qty                  | 1       |
| Outer Box Qty                  | 8       |
| Outer Box Height (mm)          | 700     |
| Outer Box Width (mm)           | 460     |
| Outer Box Depth (mm)           | 360     |
| Outer Box Weight (kg)          | 11.3    |
| Outer Box Volume               | 0.11592 |